

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
30 June 2005 (30.06.2005)

PCT

(10) International Publication Number
WO 2005/058635 A1

(51) International Patent Classification⁷: **B60N 2/28**,
B60R 22/28, 22/48

(21) International Application Number:
PCT/GB2004/005329

(22) International Filing Date:
17 December 2004 (17.12.2004)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
0329164.8 17 December 2003 (17.12.2003) GB

(71) Applicants (for all designated States except US): **BRITAX
EXCELSIOR LIMITED** [GB/GB]; 1 Churchill Way
West, Andover, Hampshire SP10 3UW (GB). **BRITAX
ROMER KINDERSICHERHEIT GMBH** [DE/DE];
Blaubeurer Strasse 71, 89077 Ulm (DE).

(72) Inventors; and

(75) Inventors/Applicants (for US only): **LANG, Heinz-Jurgen** [DE/DE]; Gansackwerweg 40, 89275 Elchingen (DE).
WETTER, Hermann [DE/DE]; Alpenstrasse 60, 89075

Ulm (DE). **CARINE, Shaun** [GB/GB]; 13 Stevens Green,
St Mary Bourne, Andover, Hampshire SP1 6DF (GB).


(74) Agent: **BROOKS, Nigel**; Hill Hampton, East Meon, Pe-
tersfield, Hampshire GU32 1QN (GB).

(81) Designated States (unless otherwise indicated, for every
kind of national protection available): AE, AG, AL, AM,
AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN,
CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI,
GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE,
KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD,
MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG,
PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM,
TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM,
ZW.

(84) Designated States (unless otherwise indicated, for every
kind of regional protection available): ARIPO (BW, GH,
GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM,
ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM),
European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI,
FR, GB, GR, HU, IE, IS, IT, LT, LU, MC, NL, PL, PT, RO,
SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN,
GQ, GW, ML, MR, NE, SN, TD, TG).

[Continued on next page]

(54) Title: **BELT TENSION INDICATOR**



(57) Abstract: A tension detector has a flexible strap (350) having its end stitched into a loop (352) that wraps round a central shaft (354). A U-shaped one-piece coil spring has two coiled end portions (356) and (358) wrapped round the shaft (354). The end portions (356) and (358) are inter-connected by a central stirrup (360). A tether strap (316) has a loop (362) sewn into its end which engages round the stirrup (360). The ends of the shaft (354) are journaled in side walls of a housing (366). Each side wall has an inwardly direct abutment projection (368). The upper surface of the housing (366) includes a window (370) through which an arcuate indicator (372) is visible. The indicator (372) has side legs (374) and (376) that are slidably mounted on the stirrup (360). When the strap (316) is relaxed, the left hand end of the arcuate indicator (372) is visible through the window (370). When the strap (316) is tightened, the arcuate indicator (372) pivots to the position shown in Figure 11 in which its right hand end, which is of a different colour to its left hand end, is visible through the window (370), indicating that the strap (316) has been tightened adequately. In the event of a crash, the coiled end portions (356) and (358) of the spring over-ride the abutment projections (368) and partially unwrap from the shaft (354) so that an extended stirrup portion (360) projects from the housing (366).



WO 2005/058635 A1



Published:

— with international search report

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.